

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number  
WO 2004/034489 A2

(51) International Patent Classification<sup>7</sup>: H01M 4/00

[IN/DE]; App.-Nr. 31, Hospitalstr. 15, 70174 Stuttgart (DE). LI, Hong [CN/DE]; App. 252, Rotebühlstr. 53, 70178 Stuttgart (DE). MAIER, Joachim [DE/DE]; Im Kazenloch 102, 75446 Wiernsheim (DE).

(21) International Application Number:  
PCT/EP2003/010138

(22) International Filing Date:  
11 September 2003 (11.09.2003)

(74) Agent: MANITZ, Finsterwald & Partner GbR; Postfach 31 02 20, 80102 München (DE).

(25) Filing Language: English

(81) Designated States (*national*): JP, US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Priority Data:  
102 42 694.5 13 September 2002 (13.09.2002) DE

(71) Applicant (*for all designated States except US*):  
MAX-PLANCK-GESELLSCHAFT ZUR [DE/DE];  
Förderung der Wissenschaften e.V., Hofgartenstrasse 8,  
80539 München (DE).

Published:  
— without international search report and to be republished upon receipt of that report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): BALAYA, Palani

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: NOVEL ELECTRODES FOR LI-BASED ELECTROCHEMICAL ENERGY STORAGE DEVICES AND A LI-BASED ELECTROCHEMICAL STORAGE DEVICE

(57) **Abstract:** The description relates to the use of at least one transition metal halide with a binder, e.g. at least one of PVDF, PTFE, PAN and ETDM and optionally with at least one conductive additive such as carbon black, graphite, metal powder and metal fibres as an electrode in an Li-based electrochemical energy storage device. Further electrode materials are also described based on ruthenium oxide, molybdenum oxide, a nano-composite composed of transition metal and lithium fluoride or lithium oxide clusters with a typical grain size of 1-10 nm.

WO 2004/034489 A2